

UC^{FIBRE} OCT D DA PE 1.0kN


Central tube cable w. 2 – 24 fibres, glass elements and LLDPE sheath.

DIN/VDE A-DQ(ZN)B2Y

NO

FR COUDEV

DK GARPE 6



Application and Installation

This cable can be used for LAN and WAN backbones, telecom access lines, fibre to business and fibre to the building drop connections as well as fibre to the home drop and access connections.

With its LLDPE sheathing this cable is ideal for outdoor installation where the installation conditions are not too difficult.

The cable features a high tensile strength and a degree of rodent protection, effective in many cases.

It is equally suited for installation in ducts and on trays. The cable is ideal for installation in tubes by blowing and flooding.

Standards

ISO 11801 2nd edition

EN 50173-1:2002

IEC 60794-1

Construction

Loose tube	ø2.8 mm jelly filled loose tube with 2 – 16 fibres; ø3.5 mm loose tube with 24 fibres			
Fibre colour code	1	Red	13	Yellow w/mark per 70 mm
	2	Green	14	White w/mark per 70 mm
	3	Blue	15	Grey w/mark per 70 mm
	4	Yellow	16	Turquoise w/mark per 70 mm
	5	White	17	Orange w/mark per 70 mm
	6	Grey	18	Pink w/mark per 70 mm
	7	Brown	19	Yellow w/mark every 35 mm
	8	Violet	20	White w/mark every 35 mm
	9	Turquoise	21	Grey w/mark every 35 mm
	10	Black	22	Turquoise w/mark every 35 mm
	11	Orange	23	Orange w/mark every 35 mm
	12	Pink	24	Pink w/mark every 35 mm
Strength member	Waterblocked E-Glass fibre elements			
Sheath	1.0 mm black LLDPE sheath, IEC 60811, IEC 60708			

Note: The Draka policy of continuous improvement may cause in changed specifications without prior notice

UC^{FIBRE} O CT D DA PE 1.0kN

Fire rating

None

Physical properties

IEC 60794-1

Nominal outer diameter	-	2 - 16 fibres: 6.0 mm 18 - 24 fibres: 6.5 mm
Nominal weight	-	2 - 16 fibres: 40 kg/km 18 - 24 fibres: 45 kg/km
Maximum installation tensile strength	E1	1000 N (fibre strain less than 1/2 of proof test level)
Short term tensile strength	E1	750 N (fibre strain less than 1/3 of proof test level)
Permanent tensile strength	E1	500 N (no attenuation change, fibre strain less than 1/4 of proof test level)
Compressive strength (crush)	E3	1500 N
Impact	E4	15 Nm (no attenuation change, no broken cable elements)
Torsion	E7	5 cycles \pm 1 turn
Kink	E10	The cables do not form a kink when a loop is drawn together to a diameter of 100 mm
Min. bending radius, unloaded	E11	R = 60 mm
Min. bending radius, loaded	-	R = 100 mm
Temperature range	F1	Storage: -40°C to +60°C Installation: -20°C to +40°C Operation: -20°C to +60°C.
Water penetration	F5B	No water on free end

Sheath marking

Draka UC^{FIBRE} O CT D DA PE 1.0 kN <Fibre count> <Fibre type><Fibre brand><Item No>05<Batch Number><Meter mark> A-DQ(ZN)B2Y <Fibre count> <Fibre family> <Mode field diameter> /125 <Transmission Class>

There is approximately 10cm space between the three blocks of text. Text string repeats every meter of the cable.

UC^{FIBRE} O CT D DA PE 1.0kN

Product codes – ordering information

Item No.	Fibre count	Product code	Fibre type	Fibre data sheet
1017451	4	UCFIBRE O CT D DA PE 1.0kN 4 MM51	OM2 50/125 multi mode 500/500	C23
1017452	8	UCFIBRE O CT D DA PE 1.0kN 8 MM51	OM2 50/125 multi mode 500/500	C23
1017071	12	UCFIBRE O CT D DA PE 1.0kN 12 MM51	OM2 50/125 multi mode 500/500	C23
1017122	24	UCFIBRE O CT D DA PE 1.0kN 24 MM51	OM2 50/125 multi mode 500/500	C23
1019213	12	UCFIBRE O CT D DA PE 1.0kN 12 OM3B	MaxCap-BB-OM3	C31
1019214	24	UCFIBRE O CT D DA PE 1.0kN 24 OM3B	MaxCap-BB-OM3	C31
1017063	4	UCFIBRE O CT D DA PE 1.0kN 4 MM61	OM1 62.5/125 multi mode	C02
1017065	6	UCFIBRE O CT D DA PE 1.0kN 6 MM61	OM1 62.5/125 multi mode	C02
1019212	8	UCFIBRE O CT D DA PE 1.0kN 8 MM61	OM1 62.5/125 multi mode	C02
1017069	12	UCFIBRE O CT D DA PE 1.0kN 12 MM61	OM1 62.5/125 multi mode	C02
1017120	16	UCFIBRE O CT D DA PE 1.0kN 16 MM61	OM1 62.5/125 multi mode	C02
1017542	24	UCFIBRE O CT D DA PE 1.0kN 24 MM61	OM1 62.5/125 multi mode	C02
1017064	4	UCFIBRE O CT D DA PE 1.0kN 4 SM2D	OS2 Single mode	C03e
1017066	6	UCFIBRE O CT D DA PE 1.0kN 6 SM2D	OS2 Single mode	C03e
1017070	12	UCFIBRE O CT D DA PE 1.0kN 12 SM2D	OS2 Single mode	C03e
1017121	24	UCFIBRE O CT D DA PE 1.0kN 24 SM2D	OS2 Single mode	C03e

Note: The Draka policy of continuous improvement may cause in changed specifications without prior notice